

IP65 WATERPROOF LED DOWNLIGHT



sales@lightideled.com | www.lightide-tech.com

FEATURE

- SMD LED
- Recessed design
- Beam Angle 120 deg., 90 deg.
- Light efficacy 120 lm/w
- Wide Input 220-240 vac, or 120-277 vac
- Waterproof IP65 rated
- Die-casting aluminum alloy housing
- Finish: white frame, grey base
- Diffuser: Froggy polycarbonate
- ETL/CETL, CE, RoHS
- Warranty: 3-5 years

SPECIFICATION

Model#	Input Voltage	Rated Power	Dimension	CUTOUT	Lumen Output
LT-WDB03-7W	220-240VAC, 120-277VAC	7W	D 95 x H 45mm	D 75 mm	840 lm
LT-WDB04-15W	220-240VAC, 120-277VAC	15W	D 115 x H 50mm	D 95 mm	1440 lm
LT-WDB05-18W	220-240VAC, 120-277VAC	18W	D 140 x H 60mm	D 115 mm	2160 lm
LT-WDB06-25W	220-240VAC, 120-277VAC	25W	D 160 x H 60mm	D 145 mm	3000 lm
LT-WDB07-30W	220-240VAC, 120-277VAC	30W	D 195 x H 60mm	D 165 mm	3600 lm
LT-WDB08-40W	220-240VAC, 120-277VAC	40W	D 230 x H 65mm	D 195 mm	4800 lm